



CABLE INOX316 - 1 X 19

vendu au mètre - **sale per meter**

Ø mm	Poids / Weight Kg / M	Charge de rupture Kg	Touret / Reel
2	0,02	300	255002
3	0,04	750	255004
4	0,08	1340	255005
5	0,12	2100	255006
6	0,18	3000	255007
7	0,24	4100	255008
8	0,32	5100	255009
10	0,49	8400	255010
12	0,71	12100	255011



CABLE INOX316 - 7 X 19

vendu au mètre - **sale per meter**

Ø mm	Poids / Weight Kg / M	Charge de rupture Kg	Touret reel
2,5	0,024	350	256002
3	0,034	470	256003
4	0,061	850	256004
5	0,095	1330	256005
6	0,138	1920	256006
8	0,243	3400	256007
10	0,381	5300	256008
12	0,548	7650	256009
14	0,746	10400	256010
16	0,975	13600	256011



CABLE INOX316 - 7 X 7

vendu au mètre - **sale per meter**

Ø mm	Poids / Weight Kg / M	Charge de rupture en Kg	Touret / Reel	En bobine / Plastic reel	
				m	réf.
1,5	0,009	130	250001	100	250401
2	0,016	230	250002	100	250402
2,5	0,026	360	250003	100	250403
3	0,035	515	250004	100	250404
4	0,063	920	250006	100	250406
5	0,098	1440	250007	100	250407
6	0,142	2070	250008	80	250408
8	0,252	3670	250009		
10	0,393	5450	250010		



CABLE INOX316 GAINE PVC BLANC - 7 X 7 WHITE PVC COATED

Cable pour filiere, souple, permettant de sécuriser le pourtour du bateau et éviter d'éventuelles chutes

Wire rope, soft, to fix the nets, to secure the deck and avoid falls.

Ø mm	Poids / Weight Kg / M	Charge de rupture Kg	Touret / Reel 200 m
3/5	0,036	515	252004
4/6	0,064	920	252005

Charge de rupture = **Breaking Load Limit**