

CHAINE - STANDARD ISO 4565 – Grade 32 / CHAIN – ISO4565 – Grade 32

| \emptyset (mm) | P1 (mm) | W1 (mm) | W (mm) | CR / BLL ² | FE/TF ³ | KG/M |
|--------------------|---------|----------|----------|-----------------------|--------------------|-------|
| 6 mm ¹ | 18 mm | 8,10 mm | 21,60 mm | 18 kN | 9,0 kN | 0,82 |
| 7 mm | 21 mm | 9,45 mm | 25,20 mm | 24 kN | 12,0 kN | 1,10 |
| 8 mm ¹ | 24 mm | 10,80 mm | 28,80 mm | 32 kN | 16,0 kN | 1,45 |
| 10 mm ¹ | 30 mm | 13,50 mm | 36,00 mm | 50 kN | 25,0 kN | 2,25 |
| 12 mm ¹ | 36 mm | 16,20 mm | 43,20 mm | 71 kN | 35,5 kN | 3,24 |
| 14 mm | 42 mm | 18,90 mm | 50,40 mm | 96 kN | 48,0 kN | 4,39 |
| 16 mm | 48 mm | 21,60 mm | 57,60 mm | 126 kN | 63,0 kN | 5,70 |
| 18 mm | 54 mm | 24,30 mm | 64,80 mm | 160 kN | 80,0 kN | 7,19 |
| 20 mm | 60 mm | 27,00 mm | 72,00 mm | 200 kN | 100,0 kN | 8,80 |
| 22 mm | 66 mm | 29,70 mm | 79,20 mm | 240 kN | 120,0 kN | 10,70 |
| 24 mm | 72 mm | 31,20 mm | 86,40 mm | 289 kN | 144,5 kN | 12,70 |
| | | | | | | |

CHAINE - STANDARD DIN766 – Grade 32 / CHAIN – DIN766 – Grade 32

| \emptyset (mm) | P1 (mm) | W1 (mm) | W (mm) | CR / BLL ² | FE/TF ³ | KG/M |
|--------------------|---------|---------|---------|-----------------------|--------------------|------|
| 6 mm ¹ | 18,5 mm | 7,2 mm | 20,4 mm | 16 kN | 8,00 kN | 0,80 |
| 7 mm | 22 mm | 8,4 mm | 23,8 mm | 25 kN | 12,50 kN | 1,10 |
| 8 mm ¹ | 24 mm | 9,6 mm | 27,2 mm | 32 kN | 16,00 kN | 1,45 |
| 10 mm ¹ | 28 mm | 12,0 mm | 36,0 mm | 50 kN | 25,00 kN | 2,30 |
| 13 mm | 36 mm | 15,6 mm | 47,0 mm | 80 kN | 40,00 kN | 3,90 |
| 14 mm | 41 mm | 16,8 mm | 50,0 mm | 100 kN | 50,00 kN | 4,40 |
| 16 mm | 45 mm | 19,2 mm | 58,0 mm | 125 kN | 62,50 kN | 5,80 |
| 18 mm | 50 mm | 21,6 mm | 65,0 mm | 160 kN | 80,00 kN | 7,40 |
| 20 mm | 56 mm | 24,0 mm | 72,0 mm | 200 kN | 100,00 kN | 9,00 |

¹ Disponible en inox / Available in stainless steel

² CR : Charge de Rupture / BLL : Breaking Load Limit

³ FE : Force d'épreuve / TF : Test force